

Jabra Evolve 20 and Evolve 20SE

Professional headset with easy call management to enhance productivity in the open office

- Great sound for calls and music
- Manage calls easily
- Flexible Plug and Play connectivity



Jabra Evolve 20

Jabra Evolve 20 Special Edition

| Detail | Information |
|----------------------------------|--|
| Packaging dimensions | L 23 x W 18 x H 3.5cm (7.09 x 9.06 x 1.38 in) |
| Weight mono / stereo | Evolve 20: 0.1425kg / 0.1711kg. Evolve 20SE: 0.1443kg / 0.1747kg |
| Whats in the box | Jabra Evolve 20/20SE Headset, Warning leaflet, Warranty leaflet, Quick start guide, USB Controller, Plastic bag for controller, Plastic bag for headset, Certified for Skype for Business sticker (Refer to BOM), Foam bag for the left earcup of the Stereo headset only, Evolve 20 with foam ear cushions/Evolve 20SE with leatherette ear cushions. |
| Battery included | No |
| AC power supply | USB power supply by PC |
| Certifications | Regulatory Approvals: CE, FCC, KCC, RCM, UL, Industrial Certifications: MS Lync, Avaya, Cisco |
| Warranty | 2 years |
| Bluetooth® device | No |
| DECT Device | No |
| NFC | No |
| Headset bandwidth | Wideband |
| Connection (mini jack, USB, etc) | USB |
| Speaker Size | D 28x3.9mm |
| Speaker sensitivity | 93.6dB SPL @1kHz |
| Speaker impedance | 32+/-4.8, @1.0kHz |
| Speaker Max Input Power | Rated Input 5mW @0.4V, max input 10mW @0.56V |
| Speaker Frequency Range | 150Hz-7kHz, @Output S.P.L -10dB |
| Microphone type | Electret Condenser Microphone |
| Microphone Sensitivity | F=1kHz, Pin=1Pa, 0dB=1V/Pa, Min=-48dB, Max=-44dB |
| Microphone Frequency Range | 100Hz ~ 10kHz @6dB |
| Speaker bandwidth Music mode | Wideband |
| Speaker bandwidth Speak mode | Wideband |
| Microphone bandwidth | Wideband |
| Cord length | Control cable: 95cm, HS cable: 120cm |
| Operating temperature | -10 °C to + 50 °C |
| Storage temperature | -30 °C to + 80 °C Storage temperature range: (-20°C to +35°C 6 months), (+35°C to +45°C 3 months), (+45°C to +45°C 1 month), (+60°C to +70°C 1 hour with no degradation), (+70°C to +85°C max. 1 hour (<20% degradation) |
| Power consumption speaker | Rated Input 5mW @0.4V, max input 10mW @0.56V |
| Features | HD Voice, PeakStop™ technology, UC plug-and-play, noise canceling microphone, HiFi sound, remote call control/easy call management, Jabra software compatible, crystal clear sound, on the ear wearing style, passive noise cancellation |

* Phone dependent

Jabra Evolve 20

| SKU | Description | EAN Code |
|--------------|---------------------------|---------------|
| 4999-823-109 | Jabra Evolve 20 MS Stereo | 5706991016970 |
| 4999-829-209 | Jabra Evolve 20 UC Stereo | 5706991016987 |
| 4993-823-109 | Jabra Evolve 20 MS Mono | 5706991016994 |
| 4993-829-209 | Jabra Evolve 20 UC Mono | 5706991017007 |

Jabra Evolve 20SE

| SKU | Description | EAN Code |
|--------------|-----------------------------|---------------|
| 4999-823-309 | Jabra Evolve 20SE MS Stereo | 5706991021158 |
| 4999-829-409 | Jabra Evolve 20SE UC Stereo | 5706991021134 |
| 4993-823-309 | Jabra Evolve 20SE MS Mono | 5706991021141 |
| 4993-823-409 | Jabra Evolve 20SE UC Mono | 5706991021127 |

Jabra.com/evolve20